

ANTIDESLIZANTE NON SLIP RUTSCHFEST	CERTIFICACIONES									CERTIFICATIONS					ZERTIFIZIERUNG											
	UNE ENV 12633 Pendulum			DIN 51130 Rampa - Pie Calzado Ramp - Shod foot Rampentest beschuht					DIN 51097 Rampa - Pie desnudo Ramp - Barefoot Rampentest Barfuß			ANSI A137.1: 2017				ASTM C1028-07			UL 410		MOHS EN 101:91 Dureza superficie Surface hardness Oberflächenhärte					
	CLASS 1	CLASS 2	CLASS 3	R-9	R-10	R-11	R-12	R-13	CLASS A	CLASS B	CLASS C	> 0,42	> 0,65	> 0,70	> 0,75	CoF. DRY ≥ 0,6 ≥ 0,7 ≥ 0,8			CoF. WET < 0,5 ≥ 0,5 ≥ 0,6 ≥ 0,7				CoF	CoF	LEVEL 4	LEVEL 5

CriSamar® STEP grabado | engraved | graviert

LUNARIS-T	•				•				•								•	•								•	
ALUMINUM-T	•				•				•									•	•								•
INCUS-T	•				•				•									•	•							•	
NEXUS-T	•				•				•									•	•							•	
OMICRON-T	•				•				•									•	•							•	
TRAPECIUS	•			•					•									•			•					•	
LUNARIS-S		•				•				•			•					•			•					•	
ALUMINUM-S		•				•				•		•						•			•					•	
INCUS-S		•				•				•				•				•			•					•	
NEXUS-S		•				•			•			•						•			•					•	
OMICRON-S	•				•					•		•						•			•					•	
CODEX		•				•					•		•					•			•					•	
VERSUS	•				•													•			•					•	
DIANA					•																						
SINUOS		•																									
LUNARIS-X								•		•			•					•			•				•		
ALUMINUM-X										•			•					•			•					•	
INCUS-X										•			•					•			•					•	
NEXUS-X										•			•					•			•					•	
OMICRON-X										•			•					•			•					•	
CODEX-X										•			•					•			•					•	

LuxRaff® Antiscratch liso | no-design | blank

LUXRAFF GRIP			•		•										0,78											•
LUXRAFF STONE	•				•					•								•			•					•
LUXRAFF SOLID	•				•					•								•			•					•
LUXRAFF REGULAR	•				•					•								•			•					•